



→ ET23SWG0002: Gas-Fired Heat Pump Water Heating & Combination System Pilot – Phase 2F – Site #1

Gas emerging technologies program (GET)



Christopher Salerno: Energy Engineer


November 20, 2024

Our Team



Cristalle Mauleon

Engineering Manager,
Lincus



Steven Long, P.E.

Director of
Engineering, ICF



**Christopher
Salerno**

Energy Engineer,
Lincus



Janik Somaiya

Energy Engineer,
Lincus

Agenda

- Introduction
- Background
- Objectives
- M&V Plan
- Baseline Data Analysis
- Results
- Planned follow on Work
- Conclusions
- Recommendations

Introduction: Gas Absorption Heat Pump Water Heaters (GAHPs)



- Study Objectives:
 - Field testing of GAHP in a DHW-only application at a multifamily building in California.
 - Address knowledge gaps: performance, cost data, and market acceptance.
- Key Findings:
 - Energy Efficiency: Reduced natural gas consumption and operational costs.
 - Practical Benefits: No need for electric panel upgrades; ideal for retrofits.
 - Adoption Barriers: Limited field data, cost clarity, and contractor familiarity.
- Impact:
 - Supports decarbonization goals and utility measure packages.
 - Offers a scalable, sustainable, cost-effective solution for modern DHW needs.

Background and Evolution of Water Heating Technologies

- Previous Field Studies Highlighting GAHP Performance:
 - NEEA (Salem, Oregon)
 - 18% gas savings, COP of 1.06, ideal for mild climates.
 - TAF (Toronto, Canada)
 - 20–50% reduction in natural gas use; 10.1 tonnes CO₂ reduction annually.
 - CEC (California)
 - Up to 50% reduction in NOx and GHG emissions, with cost advantages for energy-intensive industries.

Gaps in GAHP Applications for DHW- Only Systems

- Research Limitations
 - Focus has been on combination systems (space and water heating).
 - Lack of data for moderate climates like California where space heating is minimal.
- Key Gaps Identified:
 1. Performance Data: Limited insights into DHW-only efficiency and savings.
 2. Sizing and Integration: Knowledge gaps in optimal sizing and system integration.
 3. Maintenance Requirements: Unclear reliability and servicing needs.
 4. Cost and Payback Periods: High initial cost with uncertain ROI.
 5. Awareness and Utility Incentives: Limited promotion, incomplete measure packages.

Objective : Performance, Energy Savings, and Carbon Reduction Potential of a GAHP

- Key Objectives:

1. Energy Savings
2. Carbon Emissions
3. Performance Validation
4. Market Barrier Mitigation

- Approach:

1. Field technology assessment at a customer site with high DHW loads

Technology/Product Evaluation.




- Assessment Overview:
- Type: Field technology assessment at a customer site for realistic performance evaluation.

Assessment Activities:

1. Site Qualification.
2. Baseline Data Collection:
 - Installed M&V equipment to monitor existing system performance.
3. System Installation:
 - GAHP, controls, heat exchanger, circulation pump, and auxiliary equipment integrated into the DHW system.
4. Post-Installation Monitoring: Captured GAHP-specific data.
5. Performance Comparison: Evaluated post-installation data against baseline and EHPWH projections.

M&V Plan

- M&V Plan – Option B: Retrofit Isolation: All Parameter Measurement
- Baseline M&V Duration: 10/14/23 – 12/15/23
- ReBaseline:
 - 07/26/24–8/14/24
 - 11/12/24–11/24/24
- Post-M&V Period: 08/16/24 – 11/11/24



Baseline Analysis

- System Overview
 - Two DHW boilers:
 - i. System #1: 750 kBtuh, 80% efficient
 - ii. System #2: 650 kBtuh, 83% efficient
- Key Components
 - Two 115-gallon storage tanks
 - Constant volume pumps for boiler operation and recirculation
 - Uninsulated piping and boiler controls
- Initial Baseline Results
 - System COPs (10/14/23 – 12/15/23):
 - System #1: 0.58 | System #2: 0.68
 - Total COP: 0.62


ReBaseline Analysis

What Changed?

- Boiler #2 was replaced in July 2024, improving overall system efficiency.
- New boiler of the same efficiency and capacity as the old boiler.
- Re-baseline periods:
 - Summer (July–Aug) : 07/26/24 – 8/14/24
 - Fall (Nov) : 11/12/24 – 11/24/24
- Re-Baseline Performance
 - System COPs:
 - System #1: 0.61 | System #2: 0.75 (new boiler)
 - Total COP: 0.67


Correlation between COP and OAT

- Initial Baseline Analysis
 - Expectation: Hourly correlation between DHW System COP and OAT.
 - Finding: No correlation between COP and OAT



Correlation Between Gas Input Energy And Net Heat Output (NHO)

- Strong correlation between Gas Input Energy and Net Heat Output (NHO)
 - R^2 , CV(RSME) & NMBE meet goodness-of-fit criteria (Table Below).



- Gas Energy Input = $(1.28 * \text{NHO} + 22,835)$
- This equation forms the basis for calculating annual baseline gas energy consumption, essential for savings comparisons.

Installation Pictures

- Upper Left: Installed GAHP Unit
- Upper Right: Piping to and from HX (insulated per T24)
- Lower Left: GAHP DDC control
- Lower Right: New Concrete Pad





(L) Low water pressure DHW system #1

(R) Failed supply flow meter DHW system #1

Challenges

- Design:
 - No design support provided by mfg
 - Contractor struggled with HX size and buffer tank size
- Controls
 - Mfg has two controls
 - Contractor struggled to set up
- Site Specific Challenges
 - Water pressure regulator
 - Failed supply flow meter
 - Boiler #2 failure

Post-Installation GAHP COP Analysis

- Objective:
 - Determine the best-fitting model for GAHP COP.
- Key Findings
 - GAHP COP correlation with OAT or OAT² alone was insufficient.
 - Needed to use OAT AND NHO to get GAHP COP
 - Best-fit equation: $\text{GAHP COP} = 0.000109 * \text{NHO} + 0.0046797 * \text{OAT} - 0.02489$
 - Meets R², CV(RSME) & NMBE Criteria

Metric Name	Metric Number	Goodness of Fit Requirement
R ²	0.78	>0.70
CV(RMSE)	19%	<25%
NMBE	0.00%	- 0.05%<NMBE<0.05%



Post-Installation Gas Energy Input

- Objective:
 - Analyze hourly gas energy input post-installation.
- Correlation Equation
 - Post-Installation Gas Energy Input = $1.0513 * NHO - 488.18 * OAT + 78,106.35$
 - Meets R², CV(RSME) & NMBE Criteria

Metric Name	Metric Number	Goodness of Fit Requirement
R ²	0.93	>0.70
CV(RMSE)	7.9%	<25%
NMBE	0.00%	-0.05%<NMBE<0.05%

Post-Installation GAHP Performance Time Distribution

- Performance Insights
 - Warm-Up Period: GAHP COP reaches steady-state (~1.14) after 20 minutes of runtime.
 - Weighted Average COP: Only 0.75.
 - Average Runtime: 17.9 minutes during the post-installation period.
- Impact of Run Times
 - Shorter runtimes (<20 minutes) significantly reduce average COP.
 - Meter pulse data causes vacillations in minute-level COP values, particularly after 60 minutes.
 - Energy savings are highly sensitive to runtime duration.
- Conclusion:
 - Optimizing runtimes is critical for maximizing GAHP efficiency and achieving projected energy savings.



Post-Installation Energy Savings

Conclusion

While energy savings are below expectations, identified system adjustments and follow-on studies aim to enhance GAHP performance and energy efficiency.



- Energy Savings Overview
 - Post-Installation Net Heat Output: 233,218,011 Btu
 - Theoretical Baseline Gas Use: 347,102,703 Btu
 - Post-Installation Gas Use: 333,706,359 Btu
 - Savings: 13,396,345 Btu (134 therms, 4%)
- Key Observations
 - Savings Gap: Projected savings (30%) vs. actual (4%) due to system design and runtime limitations
- Challenges Identified:
 - Recirculation water reheating not integrated into GAHP load.
 - Site screening tools inadequately predict minimum DHW loads.
 - Short GAHP runtimes (avg. 17.9 min) hinder efficiency.
- Future Improvements
 - Incorporate recirculation DHW load into GAHP.
 - Add IST or additional hot water storage.
 - Optimize control settings to improve GAHP runtimes and efficiency.

Follow Up Work

- System Improvements:
 - Incorporate recirculation load into GAHP system.
 - Add IST or additional DHW storage.
 - Revise GAHP control settings.
- Goals:
 - Increase GAHP run-times for higher efficiency.
 - Validate lab data against field conditions.
- Future Studies:
 - Ongoing and planned field studies:
 - Hotel in Southern California. Multifamily site and additional hotel.
 - Insights from lab and field studies:
 - Optimize site selection for sufficient DHW loads. Enhance DHW system design for GAHP integration.

Conclusion

- Key Findings:
 - Post-installation COP increased to 0.70 (from 0.67).
 - Gas consumption reduced by 134 therms (4% savings).
- Challenges:
 - Contractor expertise gaps in design and installation.
 - Insufficient manufacturer support for design.
 - Short run-times limiting steady-state efficiency.
- Next Steps:
 - Enhance DHW system design and controls.
 - Train contractors on GAHP installation and site selection.
 - Leverage findings to improve GAHP adoption in utility portfolios

Thank you





Glad to be of service®



Get in touch with us: Ava Donald

Program Manager
Ava.Donald@icf.com

Follow GET on LinkedIn: [linkedin.com/cagastech](https://www.linkedin.com/company/cagastech)

Visit: cagastech.com

icf.com

 [linkedin.com/company/icf-international/](https://www.linkedin.com/company/icf-international/)

 twitter.com/icf

 <https://www.facebook.com/ThisIsICF/>

About ICF

ICF (NASDAQ:ICFI) is a global consulting and digital services company with over 7,000 full- and part-time employees, but we are not your typical consultants. At ICF, business analysts and policy specialists work together with digital strategists, data scientists and creatives. We combine unmatched industry expertise with cutting-edge engagement capabilities to help organizations solve their most complex challenges. Since 1969, public and private sector clients have worked with ICF to navigate change and shape the future.