



Research GAHP Screening Criteria & Design

Gas emerging technologies program (GET)

Alyza Khan Energy Engineer, Lincus Inc.



February 18, 2025

Our Team



Ramanujan Vetrivel

Program Manager, Lincus



Steven Long, P.E. Director of Engineering, ICF



Alyza Khan

Energy Engineer, Lincus



Cristalle Mauleon


Engineering Manager, Lincus

Agenda

- Introduction
- Background
- Research objectives
- DHW Sizing Methods
- Subject Matter Expert Interviews
- Comparison with Site Data
- GAHP Site Screening Criteria
- Conclusions

- Investigating site screening criteria and sizing methods for GAHPs in domestic hot water (DHW) systems, a novel application with unique challenges.
- Traditional DHW heaters are often oversized, while GAHPs require a minimum load to operate efficiently (recommended at 40–60% of maximum DHW load).
- Many contractors lack the expertise to size GAHPs; the project aims to provide tools for site screening, GAHP sizing, and system design to aid adoption in the multifamily sector.

Background-Site1data



Research objectives

Study Objectives:


1. Investigate DHW sizing methods in multifamily and hotel buildings in California. 2.Evaluate accuracy of these methods in calculating site-specific minimum DHW loads. 3. Analyze applicability of methods for GAHP systems and provide recommendations for improvement. 4.Develop site screening criteria and GAHP sizing tools tailored for contractors.

Expected Outcomes:

- 1. Identification of the most-used DHW sizing methods in California's multifamily and hotel/motel buildings.
- 2.Comparison of expected DHW loads from sizing methods vs. actual natural gas billing and site data.
- 3.Recommendations for key data points needed for site screening, GAHP sizing, and system design.

DHW Sizing Methods

- Literature review of DHW Sizing methods
- ASHRAE and ASPE are considered the same
- 3 manufacturer tools were considered, each with different load profiles



Outputs:

•Heat Rate [btu] Tank Size [gallons]

Analyzing DHW Sizing methods

Sizing methods: Handbooks, Codes, and Manufacturer tools.




Analyzing DHW Sizing methods

Major Findings:

- The codes have no DHW sizing calculations
- ASHRAE and ASPE share data
- Manufacturer tools & ASHRAE
 - Same demographics
 - match heat rate but not storage volume
- ASHRAE values are from 30–40 years ago

9

Comparison: ASHRAE v. Manufacturer Tools



Subject Matter Expert Interviews


Subject Matter Experts Interviewed

Type of SMEs interviewed

- Contractors
- Manufacturers
- Technical Experts

Questions

- Issues regarding sizing
- Key Components considered for sizing
- Most utilized resources
- Key components considered for selection
- Ways to account for demand increase





SME interviews

Key Findings

- •Water Heater Replacement
 - •Primary cause: Failure
 - Primary Issue: Oversizing
- •Different SMEs = Different Practices
- Key Sizing Component
 - Number of Occupants
- Preferred Sizing Tool
 - •ASHRAE's handbook
- •Top Equipment Selection Consideration
 - •Heat Rate (Capacity)
- Account for Future Demand
 - Providing space for storage
 - Ensure capacity in gas lines and electrical panels




Comparison with Site Data

• Data Sources

- Hourly gas billing data for multifamily properties in California
- Compared to ASHRAE, Manufacturer tools, and EHPWH sizing tool
- Purpose:
 - Compare max DHW loads to sizing tool recommendations.
 - Highlight inconsistent sizing by DHW tools.

13




Comparing Actual Water Heating Loads to Manufacturer Recommendations


- Site Capacity Oversizing:
 - Existing systems are oversized except at Site #4.
- ASHRAE Tool:
 - Most consistent, accurately predicts 100th percentile at most sites.
 - The team assumes 2.6 people/unit, which can overestimate usage for studios.
- Manufacturer Tools:
 - MFG #1: Usually under sizes to the 100th percentile
 - MFG #2: Closer to 99th percentile but inconsistent.
 - MFG #3: Consistently over sizes to the 100th percentile
- EHPWH Tool:
 - Consistently over sizes but aligns better at Sites #2 and #6.
- Overall Trend:
- Tools are inconsistent; ASHRAE is the most reliable.



GAHP Capacity & Minimum Flowrate




COP vs Run Time



GAHP Example

Sample Makeup Load



18

Site Screening Recommendations

•Pre-Heat Configuration:

•GAHP handles average load, gas boiler supports peak demand.

•Hot Water Demand:

Minimum flowrate required, based on GAHP capacity and temperature difference.

•Operational Efficiency:

•Continuous heating loads preferred; avoid short cycling with minimum flow rates. •GAHP performance varies by run time and cycle time.

Temperature Limitations

•Storage Tank Needs:

Indirect storage tank for GAHP + boiler system.

Buffer tank with certain MFG

Site 1 Example:

•45-minute GAHP run time achieves 94% efficiency, comparable to a condensing boiler. •Minimum flow rate for 12 cycles/day: 2.68 gal/min (3,866 gal/day).

•Feasibility of GAHP systems must be evaluated site by site using similar calculations.

Cycle Time and Tank Charge time

• Tank charge time [min] = Cycle Time [min] -GAHP run time [min]

• Min Flow Rate for 12 cycles per day $\left|\frac{gal}{min}\right| =$ GAHP Capacity [Btuh]*GAHP Run Time [hr]

 $\rho \left| \frac{lbm}{aal} \right| c_p \left[\frac{Btu}{\circ F - lbm} \right] \Delta T \left[\circ F \right] (Tank Charge Time [min])$



Minimum Flowrate, Indirect Storage & Buffer Tank Volume


• Minimum Flowrate

- Min Flow Rate $\left[\frac{Gal}{hr}\right] = \frac{GAHP \ Capacity \left[\frac{Btu}{hr}\right]}{\rho \left[\frac{lbm}{gal}\right] c_p \left[\frac{Btu}{lbm - {}^{\circ}F}\right] \Delta T \ [^{\circ}F]}$

Indirect Storage Tank Vol

— Indirect Storage Tank Vol [Gal] = GAHP Capacity [Btuh]*GAHP run time [hr]

 $\rho \left[\frac{lbm}{gal}\right] c_p \left[\frac{Btu}{^{\circ}\mathrm{F}-lbm}\right] \Delta T \ [^{\circ}\mathrm{F}]$





Conclusion

Key Takeaways:

- Inconsistent Sizing and Oversizing:
 - DHW systems often oversized.
 - Tools vary widely in predicting peak loads.
- GAHP Challenges:
 - GAHP sizing lacks a tool for predicting summer minimum load.
- ASHRAE & SME Insights:
 - ASHRAE most reliable; sizes based on occupancy.
 - Contractors rely heavily on manufacturer recommendations.
- Future Research Needs:
 - Summer load prediction methods.
 - Development of a GAHP screening and sizing tool.

22

Presentations at conferences

This research was presented at the following conferences:

2024 ETCC, California

ACEEE Hot Water and Hot Air Forum, Atlanta

ACEEE Hot Water and Hot Air Forum, Portland

Approved paper for 2025 Winter ASHRAE Conference

Thank you







Get in touch with us: **Ava Donald**

Program Manager Ava.Donald@icf.com

Follow GET on LinkedIn: linkedin.com/cagastech



icf.com

About ICF

ICF (NASDAQ:ICFI) is a global consulting and digital services company with over 7,000 full- and part-time employees, but we are not your typical consultants. At ICF, business analysts and policy specialists work together with digital strategists, data scientists and creatives. We combine unmatched industry expertise with cutting-edge engagement capabilities to help organizations solve their most complex challenges. Since 1969, public and private sector clients have worked with ICF to navigate change and shape the future.